



**FLEXAMAT INFORMATION**

Manufacturer: Motz Enterprises, Inc.  
 Product Name: Flexamat®  
 Address: 3153 Madison Road  
 Cincinnati, Ohio 45209  
 Telephone: 513-772-MOTZ (6689)  
 Fax: 513-772-6690  
 Contact: Matt Motz  
 Email: Matt@Flexamat.com  
 Website: [www.Flexamat.com](http://www.Flexamat.com)

**CONSTRUCTION NOTES:**

1. GRADE OUTFALL AREA SO THAT WATER WILL FLOW DOWN THE CENTER OF THE CHANNEL AND BE CONTAINED TO THE CHANNEL. ALL SUBGRADE SURFACES PREPARED FOR PLACEMENT OF MATS SHALL BE SMOOTH AND FREE OF ALL ROCKS, STICKS, ROOTS, OTHER PROTRUSIONS, OR DEBRIS OF ANY KIND. THE PREPARED SURFACE SHALL PROVIDE A FIRM UNYIELDING FOUNDATION FOR THE MATS WITH NO SHARP OR ABRUPT BREAKS IN THE GRADE .
2. APPLY SEED DIRECTLY TO THE PREPARED SOIL PRIOR TO FLEXAMAT INSTALLATION. USE SEED PER PROJECT SPECIFICATIONS.
3. PRIOR TO INSTALLING HEADWALL, ANCHOR TRENCH INITIAL LEADING EDGE OF MAT 18", FILL AND COMPACT ANCHOR TRENCH. INSTALL HEADWALL OVER MAT.
4. INSTALL FLEXAMAT ROLLS. AVAILABLE WIDTHS ARE 5.5', 8', 10', 12', & 16' AVAILABLE IN CUSTOM LENGTHS. A CONCRETE SAW SHALL BE USED TO CUT THE MAT TO EXACT SIZE AND SHAPE.
5. APPLICATIONS WHERE OUTFALLS FLOW INTO RETENTION PONDS, EXTEND FLEXAMAT A MINIMUM OF 3' BELOW LOW WATER ELEVATION.

Distributed by:



[www.quicksupplydm.com](http://www.quicksupplydm.com)  
 (515)289-1271

FLEXAMAT®  
 NEW OUTLET INSTALLATION  
 DETAIL